



技术参数

1. 额定电流: DCV 50mA.
2. 耐电压: 交流250伏 (50-60赫兹) 持续1分钟.
3. 接触电阻: 100毫欧max.
4. 绝缘电阻: 100兆欧min 250V DC.
5. 操作力: $450 \text{gf} \pm 100 \text{gf}$.
6. 产品寿命: 100,000次.
7. 导通行程: $1.20 \pm 0.25 \text{mm}$.
8. 操作类型: 触动回复式.

电路图

②	Terminal	3	Phosphor bronze	Au Plating		
①	Housing	1	Nylon	Black		
ITEM	PART NAME	TERN.O.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE				
DRAWN		J.X.Zhong		2013/11/11		
CHECKED						
APPROVALS						
TOLERANCES ARE		30~12.5		± 0.30		
		10~30		± 0.20		
		5~10		± 0.15		
		~5		± 0.10		
CHANGE.		CHECK.		APPRO.		
DESCRIPTION.		NEW		LED Tact Switch		
REV.		A		K6-6610D		
DATE.				SCALE: 1:1		
ECN NO.				PROJ:		
				SHEET 1 OF 1		

ELECTRONICS CO.,LTD

