



|           |       |         |
|-----------|-------|---------|
| Model No. | H=1.5 | DC-048  |
|           | H=1.1 | DC-048A |
| Schematic |       |         |

Rating:0.5A 30V DC  
 Contact Resistance:100 mΩ Max.  
 Operating temperature:−20℃~70℃  
 Operating force:3–20N  
 Operating Life:5,000cycles

|         |      |       |              |         |        |        |
|---------|------|-------|--------------|---------|--------|--------|
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
|         | A    |       | NEW          |         |        |        |

|                |                     |                     |              |
|----------------|---------------------|---------------------|--------------|
| ② Terminal     | 2                   | Phosphor bronze     | Au Plating   |
| ① Housing      | 1                   | Nylon               | Black        |
| ITEM           | PART NAME           | TERNNO.             | QTY.         |
| APPROVALS      |                     | DATE                |              |
| DRAWN          | J.X.Zhang           | 2013/11/11          |              |
| CHECKED        |                     |                     |              |
| APPROVALS      |                     |                     |              |
| TOLERANCES ARE |                     | 30 <sup>±0.15</sup> | ±0.30        |
|                | 10 <sup>±0.10</sup> | ±0.20               | ANGLE        |
|                | 5 <sup>±0.10</sup>  | ±0.15               | UNIT: mm     |
|                | ~ 5                 | ±0.10               | SCALE: 1:1   |
|                |                     |                     | PROJ.        |
|                |                     |                     | SHEET 1 OF 1 |

ELECTRONICS CO.,LTD



TITLE: PHONE JACKS

PART NO. DC-048