



### SPECIFICATIONS:

- Voltage Rating: 250V AC Min
- Current Rating: 2.0A Min
- Dielectric Strength: 1000V AC For 1Minute
- Insulation Resistance: 1000Megohms Min
- Contact Resistance: 30Milliohms Max
- Operation Temperature: -55°C To +125°C
- Product Withstanding Reflow Soldering: 260°C For 15s
- Durability :5000 Cycles
- Normal Force At Working Position: 80g Min
- Insertion Force:>3N
- Insulator: High Temperature Thermoplastic
- UL 94V-0 Black (LCP Black)
- Contact: Beryllium Copper,
- Gold Flash Over Nickel

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
②	Terminal	—	5	Phosphor Bronze	Au Plated	—
①	Housing	—	1	LCP	Black	—

APPROVALS	DATE	TITLE:
DRAWN	xu qi feng 2014.12.04	电池座 3P
CHECKED		
APPROVALS		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
TOLERANCES ARE						
		30~12.5	±0.30	ANGLE		PART NO. BC-1-3P
		10~30	±0.25			SCALE: 1:1
		5~10	±0.20			UNIT: mm
		~5	±0.15			DRAWING NO.
						PROJ: ①
						SHEET 1 OF 1

**HRON**  
ELECTRONICS CO.,LTD